



MOTOTRBO™ DP2000e SERIES

YOU'RE MORE PRODUCTIVE, CONNECTED

With this dynamic evolution of MOTOTRBO digital two-way radios, you're better connected, safer and more efficient. The DP2000e Series is designed for the everyday worker who needs effective communications. With systems support and loud, clear audio, these next-generation radios deliver cost-effective connectivity to your organisation.

CONNECTED

The MOTOTRBO DP2000e Series is a family of DMR-standard digital radios that delivers operations-critical voice communications. With support for basic trunking as well as legacy analogue technology, you can keep your organisation connected as it grows.

SAFE

The DP2000e Series is designed to improve safety in your organisation, with the rapid response capability of instant push-to-talk communications. Even if a worker is unresponsive, you can remotely activate the radio to check that your worker is safe. Privacy options are available to protect your communications, and radios can be remotely disabled if they are misplaced. New HazLoc models are available for use in areas where flammable or explosive materials are present.

EFFICIENT

With new noise cancellation technology and enhanced clarity, the DP2000e Series delivers excellent audio quality to make your workplace communications clearly intelligible. The latest energy technology delivers up to 28 hours of battery life for 3-shift working, and the optional IMPRES Over-the-Air Battery Management tool helps you maximise battery lifetime. An improved receiver boosts range, allowing you to reach further than ever.



WHAT'S NEW IN THESE NEXT GENERATION RADIOS

- Enhanced audio quality
- Improved expandability
- Better battery life (up to 28 hours)
- Better range
- Better waterproofing (IP67)
- HazLoc models available

PRODUCT DATA SHEET
MOTOTRBO™ DP2000e SERIES
DIGITAL TWO-WAY RADIOS



| | Limited Keypad (LKP) Model | | No Keypad (NKP) Model | |
|--|-----------------------------------|---------------|------------------------------|---------------|
| Model Number | DP2600e | | DP2400e | |
| Band | VHF | UHF | VHF | UHF |
| GENERAL SPECIFICATIONS | | | | |
| Frequency | 136-174 MHz | 403-527 MHz | 136-174 MHz | 403-527 MHz |
| High Power Output | 5 W | 4 W | 5 W | 4 W |
| Low Power Output | 1 W | 1 W | 1 W | 1 W |
| Channel Spacing | 12.5, 20, 25 kHz | | | |
| Channel Capacity | 128 | | 16 | |
| Dimensions (H x W x D), Radio + Standard 2250 mAh Battery | 122 x 56 x 42 mm | | 122 x 56 x 42 mm | |
| Weight, Radio + Standard 2250 mAh Battery | 305 g | | 288 g | |
| Dimensions (H x W x D), Radio + Slim 2050 mAh Battery | 122 x 56 x 36 mm | | 122 x 56 x 36 mm | |
| Weight, Radio + Slim 2050 mAh Battery | 287 g | | 270 g | |
| Dimensions (H x W x D), Radio + High Capacity 3000 mAh Battery | 122 x 56 x 42 mm | | 122 x 56 x 42 mm | |
| Weight, Radio + High Capacity 3000 mAh Battery | 309 g | | 292 g | |
| Digital / Analogue Battery Life ¹ , Standard 2250 mAh Battery | 21.5 / 16 hrs | 20.5 / 16 hrs | 21.5 / 16 hrs | 20.5 / 16 hrs |
| Digital / Analogue Battery Life ¹ , Slim 2050 mAh Battery | 19.5 / 14 hrs | 18.5 / 14 hrs | 19.5 / 14 hrs | 18.5 / 14 hrs |
| Digital / Analogue Battery Life ¹ , High Capacity 3000 mAh Battery | 28.5 / 21 hrs | 27.5 / 21 hrs | 28.5 / 21 hrs | 27.5 / 21 hrs |
| Power Supply (Nominal) | 7.5 V | | | |



PRODUCT DATA SHEET
MOTOTRBO™ DP2000e SERIES
DIGITAL TWO-WAY RADIOS

ALL MODELS

TRANSMITTER SPECIFICATIONS

| | |
|--|--|
| 4FSK Digital Modulation | 12.5 kHz Data: 7K60F1D and 7K60FXD, 12.5 kHz Voice: 7K60F1E and 7K60FXE, Combination of 12.5 kHz Voice and Data: 7K60F1V |
| Digital Protocol | ETSI TS 102 361-1, -2, -3 |
| Conducted/Radiated Emissions (TIA603D) | -36 dBm < 1GHz, -30 dBm > 1GHz |
| Adjacent Channel Power | 60dB (12.5 kHz channel), 70dB (20 and 25 kHz channel) |
| Frequency Stability | ± 0.5 ppm |

RECEIVER SPECIFICATIONS

| | |
|--|---|
| Analogue Sensitivity (12dB SINAD) | 0.16 uV |
| Digital Sensitivity (5% BER) | 0.14 uV |
| Intermodulation (TIA603D) | 70 dB |
| Adjacent Channel Selectivity, (TIA603A)-1T | 60 dB (12.5 kHz channel), 70 dB (20 and 25 kHz channel) |
| Adjacent Channel Selectivity, (TIA603D)-2T | 45 dB (12.5 kHz channel), 70 dB (20 and 25 kHz channel) |
| Spurious Rejection (TIA603D) | 70 dB |

AUDIO SPECIFICATIONS

| | |
|--|---|
| Digital Vocoder Type | AMBE+2™ |
| Audio Response | TIA603D |
| Rated Audio | 0.5 W |
| Audio Distortion at Rated Audio | 3% |
| Hum and Noise | -40 dB (12.5 kHz channel), -45 dB (20 and 25 kHz channel) |
| Conducted Spurious Emissions (TIA603D) | -57 dBm |

ENVIRONMENTAL SPECIFICATIONS

| | |
|------------------------------------|--------------------------------|
| Operating Temperature ² | -30 °C to +60 °C |
| Storage Temperature | -40 °C to +85 °C |
| Electrostatic Discharge | IEC 61000-4-2 Level 4 |
| Dust and Water Intrusion | IEC 60529 - IP67, 1 m for 1 hr |
| Packaging Test | MIL-STD 810D and E |

HAZLOC CERTIFICATION

DP2000e Series radios are UL-Approved to TIA-4950 for use in Hazardous Locations, Division 1, Class I, II, III, Groups C,D,E, F, G; Division 2, Class 1, Groups A,B,C,D when properly equipped with Motorola UL-Approved battery.

CONNECTION

- VHF Band, 5 W
- UHF Band, 4 W
- LKP Models: Mono screen, limited keypad, 128 channels
- NKP Models: No screen or keypad, 16 channels
- Analogue and Digital
- Voice and text only
- Canned Text Messaging
- Voice Announcement
- Home Channel Reminder

AUDIO

- Intelligent Audio
- IMPRES Audio
- SINC+ Noise Cancellation
- Acoustic Feedback Suppressor
- User-Selectable Audio Profiles
- Trill Enhancement
- Switch Speaker

CUSTOMISATION

- Wide range of Accessories
- 4 Programmable Buttons (2 for NKP model)

MANAGEMENT

- Radio Management
- Over-the-Air Programming
- IMPRES Energy
- IMPRES Battery Management
- Over-the-Air Battery Management

SAFETY

- Lone Worker
- Basic Privacy
- Enhanced Privacy
- Transmit Interrupt (Decode only)
- Digital Emergency
- Emergency Search Tone
- Remote Monitor (Decode only)
- Radio Disable / Enable (Decode)
- HazLoc certification
- Waterproof to IP67
- Rugged to MIL-STD 810

SYSTEMS

- Dual Capacity Direct Mode
- Conventional
- IP Site Connect
- Capacity Plus

- Optional

NOTES

1: Typical battery life, 5/5/90 profile at maximum transmitter power with Wi-Fi disabled. Actual observed runtimes may vary.

2: Specialized low-temperature battery required for operation below -10 °C

Specifications subject to change without notice. All specifications shown are typical values.

MILITARY STANDARDS

| | MIL-STD 810C | | MIL-STD 810D | | MIL-STD 810E | | MIL-STD 810F | | MIL-STD 810G | |
|-----------------|--------------|---------------|--------------|--------------|--------------|--------------|--------------|---------------|--------------|--------------|
| | METHOD | PROCEDURE | METHOD | PROCEDURE | METHOD | PROCEDURE | METHOD | PROCEDURE | METHOD | PROCEDURE |
| Low Pressure | 500.1 | I | 500.2 | II | 500.3 | II | 500.4 | II | 500.5 | II |
| High Temp | 501.1 | I, II | 501.2 | I/A1, II/A1 | 501.3 | I/A1, II/A1 | 501.4 | I/Hot, II/Hot | 501.5 | I/A1, II/A1 |
| Low Temp | 502.1 | I | 502.2 | I/C3, II/C1 | 502.3 | I/C3, II/C1 | 502.4 | I/C3, II/C1 | 502.5 | I/C3, II/C1 |
| Temp Shock | 503.1 | I | 503.2 | A1/C3 | 503.3 | A1/C3 | 503.4 | I | 503.5 | I-C |
| Solar Radiation | 505.1 | II | 505.2 | I/Hot-Dry | 505.3 | I/Hot-Dry | 505.4 | I/Hot-Dry | 505.5 | I/A1 |
| Rain | 506.1 | I, II | 506.2 | I, II | 506.3 | I, II | 506.4 | I, III | 506.5 | I, III |
| Humidity | 507.1 | II | 507.2 | II/Hot-Humid | 507.3 | II/Hot-Humid | 507.4 | - | 507.5 | II/Hot-Humid |
| Salt Fog | 509.1 | I | 509.2 | I | 509.3 | I | 509.4 | - | 509.5 | - |
| Dust | 510.1 | I, II | 510.2 | I, II | 510.3 | I, II | 510.4 | I, II | 510.5 | I, II |
| Vibration | 514.2 | VIII/F, W, XI | 514.3 | I/10, II/3 | 514.4 | I/10, II/3 | 514.5 | I/24, II/5 | 514.6 | I/24, II/5 |
| Shock | 516.2 | II | 516.3 | I, IV | 516.4 | I, IV | 516.5 | I, IV | 516.6 | I, IV |

REMOTE SPEAKER MICROPHONES

Improve usability with a Remote Speaker Microphone (RSM). Choose from standard, heavy duty and noise-cancelling models, with or without secondary earpiece connector.



ENERGY SOLUTIONS

Make sure your radio is powered and charged properly, with our range of energy solutions. Choose from single and multi-unit chargers, and slim and high capacity batteries.



CARRY SOLUTIONS

However you choose to wear or carry your radio, we have a solution for you. From leather cases to belts and belt clips to bags, straps and pouches.



HEADSETS

In a noisy workplace, you need to protect your workers' hearing. Whether it's heavy duty noise reduction or innovative temple transducer technology, our headsets can help.



COVERT ACCESSORIES

When you need to stay in touch discreetly, choose from our range of covert audio accessories. From clear tube earpieces to virtually invisible wireless in-ear units.



VIBRATING BELTCLIP

When it's unacceptable to miss calls in a noisy environment, equip your radios with a powerful vibrating belt clip for an extra physical alert.



For details on these and other DP2000e Series accessories, please download the MOTOTRBO Professional Accessories Catalogue.

To get connected with MOTOTRBO, please contact your local Motorola representative or visit motorolasolutions.com.au

Motorola Solutions Australia Pty Limited.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylised M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2016 Motorola, Inc. All rights reserved. 02-2016_HD

MOTOTRBO™
DIGITAL REMASTERED.